Application No. 09/945,483   Attorney Docket
No. 66251

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of the claims in the application:

1. (Original) A method of increasing utilization of user link bandwidth for a code division multiple access communications system comprising the steps of:

selecting a set of orthogonal complex codes each having a code length that is greater than a code length of an optimum real code and less than or equal to a spreading code length; and

transferring symbols across at least one of a plurality of user links to or from at least one of a corresponding plurality of user terminals wherein the symbols are represented by a corresponding one of the set of orthogonal complex codes.

2. (Original) The method of Claim 1 wherein the set of orthogonal complex codes is generated from a Kronecker tensor product given by formula:

$$C_{LXP} = A_L \otimes W_P$$

wherein

C_{LXP} is a matrix of orthogonal complex codes wherein each of the orthogonal complex codes has a code length equal to $L \times P$,

L is a positive integer,

P equals 2^n where n equals a positive integer,

W_P is a Walsh code matrix for a code length of P,

A_L is a matrix of coefficients a_{jk} wherein j is a row index equal to 1 ... L, k is a column index equal to 1... L, and

$$a_{jk} = e^{j2\pi(j-1)(k-1)/L}.$$

3. (Original) The system of Claim 1 wherein the corresponding one of the set of orthogonal complex codes has a code length of 12.

2

4. (Original) The system of Claim 1 wherein the spreading code has a code length of 12.

5. (Original) A code division multiple access communications system comprising:

a base station;

a geo-stationary platform;

a feeder link coupled to the base station and the geo-stationary platform for transferring symbols between the base station and the geo-stationary platform;

a plurality of user terminals; and

a plurality of user links coupled respectively to the plurality of user terminals and to the geo-stationary platform for transferring symbols between the geo-stationary platform and at least one of the plurality of user terminals wherein the symbols are represented by at a corresponding one of a set of orthogonal complex codes having a code length that is greater than a code length of an optimum real code and less than or equal to a spreading code length.

6. (Original) The system of Claim 5 wherein the set of orthogonal complex codes is generated from a Kronecker tensor product given by:

$$C_{LXP} = A_L \otimes W_P$$

wherein

C_{LXP} is a matrix of orthogonal complex codes wherein the at least one of the orthogonal complex codes has a code length equal to $L \times P$,

L is a positive integer,

P equals 2^n and n equals a positive integer,

W_P is a Walsh code matrix for a code length of P,

A_L is a matrix of coefficients a_{jk}, where j is a row index equal to $1 \ldots L$, k is a

3

Application No. 09/945,483   Attorney Docket
No. 66251

column index equal to 1... L, and

$$a_{jk} = e^{j2\pi(j-1)(k-1)/L} .$$

      7. (Original) The system of Claim 5 wherein the at least one of the set of orthogonal complex codes has a code length of 12.

      8. (Original) The system of Claim 5 wherein the spreading code has a code length of 12.

      9. (Original) A method of increasing utilization of user link bandwidth in a code division multiple access communications system comprising the steps of:

      selecting a spreading code length; and

      selecting a set of orthogonal complex codes each having a code length that is greater than a code length of an optimum real code and less than or equal to the spreading code length.

      10. (Original) The method of Claim 9 further comprising the step of transferring symbols across a user link to or from a user terminal wherein the symbols are represented by a corresponding one of the set of orthogonal complex codes.

4